

Seated Height AV Lecterns

Technical Sales Brochure

Seated-height lecterns are designed to provide comfortable presentation surfaces for speakers who prefer to sit while addressing an audience. These lecterns are adjustable to ensure optimal positioning and facilitate seamless communication d



66-LP303647LM-RWGSC



66-LP303647LM-FPA2124NK



Trolley™ Up

66-LS266030LD TE0728NK



Trolley™ Down



(217) 342-7070


www.novadesk.com

sales@novasolutionsinc.com

Sit/Stand AV Lecterns

Available with all Visual Display Options

Locking iMod™ modesty rear access panels. Wire management and power strip. Locking doors. Vent Fan cutouts in rack rail storage bottom shelf (Vent fans sold separately). 12 RU rack rails in far right compartment: 19 ¼" W. Front and Rear Rack Rails. For left-handed units add "-L" to end of model number. Add (-N) to the end of all model numbers for all non-locking. Available with heavy duty casters (Specify "-C") **NOTE: Adding Casters will increase height of lectern by 2 ¾".**



- Electrically adjustable unit from 30" base height with 12" travel.
- ADA compliant.
- System lift capacity up to 550 lbs.
- Column legs are standard Polished Black metal.

1. Select model number

Ex: 67-LS303641LM

(30x36x41 Lectern with pull-out shelf and laminate modesty)

2. Select laminate color for base and worksurface

If ordering with perforated metal modesty, select metal color

Note: Laminate modesty will match base color.

Ex: 129 664 PSL
 Base Worksurface Metal


Optional Selections:

3. Select Visual Display Options

Ex: TE0728NK (The Trolley™ EXL with NOVA keyboard drawer)

4. Select Options and Factory Installed Accessories

Ex: RWGSC (Star cut wire grommet)




D x W x H (in.) ft³ / lbs Model

Lectern will grow 2" in width when ordered with FPA2124


Laminate Modesty

30 x 58 ¾ x 30 39.8 / 360 66-SS305730LX



Perforated Metal Modesty (shown left)

30 x 58 ¾ x 30 39.8 / 360 66-SS305730MX




Privacy Sides w/ Laminate Modesty

30 x 58 ¾ x 34 42.9 / 368 66-SSP305934LX

Privacy Sides w/ Perforated Metal Modesty

30 x 58 ¾ x 34 42.9 / 368 66-SSP305934MX




CPU shelf. CPU storage width: 8 ½"

Only available with Trolley™ E, or Surface Mount Arm Visual Display Options. **Note: ADA Height Compliant Only**


Laminate Modesty

30 x 58 ¾ x 30 39.8 / 379 66-SS305730LC



Perforated Metal Modesty (shown left)

30 x 58 ¾ x 30 39.8 / 379 66-SS305730MC



Locking CPU door. CPU storage width: 8"


(Reduced with some Visual Display Options)

CPU Storage Width by Visual Display Option:

FPA2124 - 6 ½" W


Laminate Modesty

30 x 67 7/16 x 30 45.1 / 398 66-SS306530LD



Perforated Metal Modesty (shown left)

30 x 67 7/16 x 30 45.1 / 398 66-SS306530MD



Privacy Sides w/ Laminate Modesty

30 x 67 7/16 x 34 49.3 / 406 66-SSP306834LD

Privacy Sides w/ Perforated Metal Modesty

30 x 67 7/16 x 34 49.3 / 406 66-SSP306834MD

Model Number Structure

66	-	LS	305730	LC
Series		Type	Size	Modesty Combination for
66=Lectern		SS= Sit/Stand Lectern PS= Prestige Sit/Stand	D x W x H	Laminate modesty
				LD=Laminate modesty panels & CPU compartment with door LX=Laminate modesty; No CPU shelf LC=Laminate modesty panels & CPU shelf
				Modesty Combination for
				Perforated Metal modesty
				MD=Metal modesty panels & CPU compartment with door MX=Metal modesty; No CPU shelf MC=Metal modesty panels & CPU shelf


Grommets

Standard grommets are rectangular black plastic.


Prestige Sit-Stand AV Lectern

Worksurface base height at 32" H. Available with casters. Specify "-C". Adding casters will not affect rack space. Add (-N) to the end of all model numbers for all non-locking.

D x W x H (in.) ft³ / lbs Model
30 x 66 x 39 43.0 / 400 66-PSS306639LX



Shown with casters






ASSEMBLY REQUIRED

Visual Display Options

Adding a Downview™ or Trolley™ Visual Display Option may affect CPU storage width or available RUs



The Trolley™

- Ships installed in assembled units only.
- Maximum distance from center of wall mount VESA plate to bottom of monitor is 6 3/4" (171mm)

The Trolley™ E

Maximum Dimensions for Widescreen:
2 1/2" D x 18 7/8" W x 14 1/2" H
up to 20" widescreen

The Trolley™ EXL

Maximum Dimensions for Widescreen:
2 1/2" D x 22 7/8" W x 14 1/2" H
up to 24" widescreen
36" min. worksurface width

- Patented Access door automatically opens and closes with the push of a button
- Low voltage electrical motor to lift & lower monitor
- Intelligent Motion Technology™ provides operational intuition

Model	Wt(lbs)	Description
-------	---------	-------------

With NOVA Keyboard Drawer


NOVA Keyboard Drawer installed in assembled units only.

International Customers: The Trolley™ includes Universal Power Control Units, compatible with all power requirements inside and outside the U.S.

TE0724NK	48	Trolley™ E & NOVA Keyboard Drawer
----------	----	-----------------------------------

TE0728NK	48	Trolley™ EXL & NOVA Keyboard Drawer
----------	----	-------------------------------------

Available with NOVA Linked™



Downview™

- Ships installed in assembled units only.

16" D x 21" W viewport (Widescreen)

Maximum Dimensions for Widescreen: 20 1/8" W x 12 1/2" H
up to 21" widescreen

24" min. worksurface depth

18" D x 21" W viewport (Widescreen)

Maximum Dimensions for Widescreen: 20 1/8" W x 14 1/2" H
up to 21" widescreen

26" min. worksurface depth

21" D x 24" W viewport (Widescreen)

Maximum Dimensions for Widescreen: 23 1/8" W x 19" H
up to 24" widescreen

30" min. worksurface depth

36" min. worksurface width

- Tinted, tempered glass viewport
- Keeps monitor under glass below worksurface
- Ergonomic viewing angle

Model	Wt(lbs)	Description
-------	---------	-------------

With NOVA Keyboard Drawer


Downview™ & NOVA Keyboard Drawer installed in assembled units only.

Optional Privacy/Glare visor sold separately.

FPA1621NK	35	16" D x 21" W Downview™ & NOVA Keyboard Drawer
-----------	----	--

FPA1821NK	35	18" D x 21" W Downview™ & NOVA Keyboard Drawer
-----------	----	--

FPA2124NK	39	21" D x 24" W Downview™ & NOVA Keyboard Drawer
-----------	----	--



Surface Mount Arm

- Installation required

Surface Mount Arm

Maximum Weight: 21 lbs
Maximum Dimensions: Up to 24" widescreen

- Securely fastens monitor to worksurface
- Height and tilt adjustable

Articulating Surface Mount Arm

Maximum Weight: 33 lbs
Maximum Dimensions: Up to 35" widescreen

Model	Wt(lbs)	Description
-------	---------	-------------

With NOVA Keyboard Drawer

NOVA Keyboard Drawer installed in assembled units only.

SMA0203NK	13	SMA & NOVA Keyboard Drawer
-----------	----	----------------------------

ASMA0203NK	22	Articulating SMA & NOVA Keyboard Drawer
------------	----	---




ASSEMBLY REQUIRED

Options & Accessories

Options for Lecterns

Flip-up Shelf



D x W x H (in.) **ft³ / lbs** **Model** **List Price**
Field installed on all but Sit-Stand Lecterns. Shipped Separately. Color matches worksurface of lectern ordered. Located 3" down from worksurface. For factory prep, must specify "U" on lectern model number for left-handed, or "V" on lectern model number for right-handed placement, or "B" on lectern model number for both left and right hand placement.


For 21" D or 24" D Lectern:

Attaches to the LEFT side panel of Lectern			
20 x 20 x 1	0.9 / 24	66-SH202001L	
Attaches to the RIGHT side panel of Lectern			
20 x 20 x 1	0.9 / 24	66-SH202001R	

For 26" D, 30" D or 36" D Lectern:

Attaches to the LEFT side panel of Lecterns			
22 x 20 x 1	1.0 / 24	66-SH222001L	
Attaches to the RIGHT side panel of Lecterns			
22 x 20 x 1	1.0 / 24	66-SH222001R	


2 Space Rack Drawer



Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.

20 x 15 x 3 1/2	10.4 / 20	66-2DRAWER	
-----------------	-----------	------------	--


Sliding Shelf



Attaches to rack rails. 35 lb. weight capacity.

20 x 15 x 1	10.4 / 15	66-SSHELF	
-------------	-----------	-----------	--


2 Space Rack Shelf



Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.

20 x 15 x 3 1/2	10.4 / 15	66-2SHELF	
-----------------	-----------	-----------	--

Removable Console



Black laminate box (Customer to provide cutouts needed)

11 x 15 x 6	2.0 / 20	66-CONSOLE01	
-------------	----------	--------------	--


Ventilation Fan



115V fan rated at 57 CFM. 30 dBA. Add (-VF) on lectern model number to be factory installed. Must also specify cutout location on lectern.

1 x 6 x 6	2.0 / 3	66-FAN	
-----------	---------	--------	--

Rack Cube




All metal construction providing front and rear Rack Rails allowing rack storage mounting prior to installation in rack storage compartment. Standard Black metal. Available with 6 RU - 14 RU; height varies by RU count. **Complete Model number replacing blank "___" with desired RU** (Ex: 66-RRCUBE10 - 10 RU Rack Cube). **NOTE:** If ordering with a lectern, specify "-RR" at end of lectern model number. (Ex: 66-LP303047LM-RR)

19 1/2 x 19 1/2 x Varies		66-RRCUBE_	
--------------------------	--	------------	--

Factory Installed Accessories

Must specify location of grommet / power center at time of order

Factory Installed NOVA Keyboard Drawer



Dimensions (in.)	Model
Keyboard length to fit desk ordered. Only ordered when NO Visual Display Option is chosen	
24" - 34" wide	NK

Rectangular Wire Grommet



Rectangular black plastic grommet cover is removable for easy wire management

1 7/8" D x 3 1/4" W	WG1080
---------------------	--------

Star Cut Wire Grommet



Round black plastic grommet with rubber star cut opening allows more cords and cables to pass through

2 3/4" Diameter	RWGSC
-----------------	-------

Pop-up Power Center



Two grounded outlets. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed.

3 3/4" D x 5" W	11225PP
-----------------	---------

Pop-up Power / Data Center



One grounded outlet. One opening for voice/data jack. Voice/Data Adapter Kit (included) provides adapters for couplers & jacks from a variety of manufacturers. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed.

3 3/4" D x 5" W	11225PD
-----------------	---------

Pop-up Power / USB Charging Center



One grounded outlet. One USB charging duplex. Fluid one touch accessibility. 6ft, 15 Amp cord. UL Listed.

3 3/4" D x 5" W	11225PC
-----------------	---------

Round Flush Power Center



Two grounded outlets. Clean, flush mount. 6ft, 15 Amp cord. UL listed.

4" Diameter	3359PP
-------------	--------

Round Flush Power / USB Charging Center



One grounded outlet. One USB charging duplex. Clean, flush mount. 6ft, 15 Amp cord. UL Listed.

4" Diameter	3359PC
-------------	--------

Round Power Center



One grounded outlet. Features spill-proof technology. 6ft, 15 Amp cord. UL Listed.

2" Diameter	3825P
-------------	-------