

# Privacy Sides AV Lecterns

## with Pull-out Shelf & Trolley



### Model Number Structure

67	-	LP	304847	LM	TE0728NK
<u>Series</u>		<u>Type</u>	<u>Size</u>	<u>Modesty Combination for</u>	<u>Visual Display Option</u>
67=Lectern with Pull-out Shelf		LP= Lectern with Privacy Sides	D x W x H	<u>Laminate modesty</u> LM=Laminate modesty <u>Perforated Metal modesty</u> MM=Metal modesty	TE0724NK=Trolley™ E & NOVA Keyboard Drawer TE0728NK=Trolley™ EXL & NOVA Keyboard Drawer



(217) 342-7070  
www.novadesk.com  
sales@novasolutionsinc.com

# Privacy Sides AV Lecterns

## 1. Select model number

Ex: 67-LP304847LM

(30x48x47 Privacy Sides AV Lectern with Pull-out Shelf & laminate modesty)

## 2. Select laminate color for base and worksurface


If ordering with perforated metal modesty, select metal color Note:

Laminate modesty will match base color.

Ex: 567 567  
Base Worksurface

## Optional Selections:

3. Select Visual Display Options (see page 34) Ex: TE0728NK (The Trolley™ EXL with NOVA keyboard drawer)



20 RU rack rails


D x W x H (in.)	ft <sup>3</sup> / lbs	Model
<b>Laminate Modesty</b>		
30 x 48 x 47 7/8	48.6 / 525	67-LP304847LM
36 x 48 x 47 7/8	57.7 / 585	67-LP364847LM
<b>Perforated Metal Modesty</b>		
30 x 48 x 47 7/8	48.6 / 525	67-LP304847MM
36 x 48 x 47 7/8	57.8 / 585	67-LP364847MM

## Pull-out shelf Interior Dimensions:

30" D Lecterns: 22 1/4" D x 20 3/8" W x 7 3/4" H  
36" D Lecterns: 28 1/4" D x 20 3/8" W x 7 3/4" H

## Storage Dimensions:

48" W Unit: Left compartment w/ rack rails - 25 3/4" W. Right compartment w/ rack rails - 19 1/4" W



## The Trolley™

- Ships installed in assembled units only. Maximum distance from center of
- wall mount VESA plate to bottom of monitor is 6 3/4" (171mm)

## The Trolley™E Maximum Dimensions for

### Widescreen:

2 1/2" D x 18 1/4" W x 14 1/2" H up to  
20" widescreen

## The Trolley™ EXL Maximum Dimensions for

### Widescreen:

2 1/2" D x 22 7/8" W x 14 1/2" H up to  
24" widescreen  
36" min. worksurface width

## Model Wt(lbs) Description

### With NOVA Keyboard Drawer

NOVA Keyboard Drawer installed in assembled units only.

International Customers: The Trolley™ includes Universal Power Control Units, compatible with all power requirements inside and outside the U.S.

TE0724NK	48	Trolley™ E & NOVA Keyboard Drawer
TE0728NK	48	Trolley™ EXL & NOVA Keyboard Drawer

Available with NOVA Linked™

## Standard Features

- iMod™ wire management
- Locking Front Access Doors
- Heavy Duty Locking Casters
- Powerstrip
- Laminate or metal modesty panel
- 20 Rack Units
- Ships Fully Assembled (Casters Field Installed)
- Privacy Sides

## Color Options

### Base Color Options



### Worksurface Color Options



### Metallic Color Options (for Metal Modesty)











# Options & Accessories

## Factory Installed Accessories

**Must specify location of grommet / power center at time of order**

		Dimensions (in.)	Model
NOVA Keyboard Drawer		Keyboard length to fit desk ordered. Only ordered when NO Visual Display Option is chosen	
		24" - 34" wide	NK
Rectangular Wire Grommet		Rectangular black plastic grommet cover is removable for easy wire management	
		1 7/8" D x 3 1/4" W	WG1080
Star Cut Wire Grommet		Round black plastic grommet with rubber star cut opening allows more cords and cables to pass through	
		2 3/4" Diameter	RWGSC
Pop-up Power Center		Two grounded outlets. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed.	
		3 3/4" D x 5" W	11225PP
Pop-up Power / Data Center		One grounded outlet. One opening for voice/data jack. Voice/Data Adapter Kit (included) provides adapters for couplers & jacks from a variety of manufacturers. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed.	
		3 3/4" D x 5" W	11225PD
Pop-up Power / USB Charging Center		One grounded outlet. One USB charging duplex. Fluid one touch accessibility. 6ft, 15 Amp cord. UL Listed.	
		3 3/4" D x 5" W	11225PC
Round Flush Power Center		Two grounded outlets. Clean, flush mount. 6ft, 15 Amp cord. UL listed.	
		4" Diameter	3359PP
Round Flush Power / USB Charging Center		One grounded outlet. One USB charging duplex. Clean, flush mount. 6ft, 15 Amp cord. UL Listed.	
		4" Diameter	3359PC
Round Power Center		One grounded outlet. Features spill-proof technology. 6ft, 15 Amp cord. UL Listed.	
		2" Diameter	3825P

## Options for Lecterns

	D x W x H (in.)	ft <sup>3</sup> / lbs	Model	List Price
<b>Flip-up Shelf</b> 	Field installed on all but Sit-Stand Lecterns. Shipped Separately. Color matches worksurface of lectern ordered. Located 3" down from worksurface. For factory prep, must specify "U" on lectern model number for left-handed, or "V" on lectern model number for right-handed placement, or "B" on lectern model number for both left and right hand placement.			
	For 21" D or 24" D Lectern:			
	Attaches to the LEFT side panel of Lectern			
	20 x 20 x 1	0.9 / 24	66-SH202001L	
	Attaches to the RIGHT side panel of Lectern			
<b>2 Space Rack Drawer</b> 	For 26" D, 30" D or 36" D Lectern:			
	Attaches to the LEFT side panel of Lecterns			
	22 x 20 x 1	1.0 / 24	66-SH222001L	
	Attaches to the RIGHT side panel of Lecterns			
	22 x 20 x 1	1.0 / 24	66-SH222001R	
<b>Sliding Shelf</b> 	Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.			
	20 x 15 x 3 1/2	10.4 / 20	66-2DRAWER	
<b>2 Space Rack Shelf</b> 	Attaches to rack rails. 35 lb. weight capacity.			
	20 x 15 x 1	10.4 / 15	66-SSHELF	
<b>Removable Console</b> 	Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.			
	20 x 15 x 3 1/2	10.4 / 15	66-2SHELF	
<b>Ventilation Fan</b> 	Black laminate box (Customer to provide cutouts needed)			
	11 x 15 x 6	2.0 / 20	66-CONSOLE01	
<b>Rack Cube</b> 	115V fan rated at 57 CFM. 30 dBA. Add (-VF) on lectern model number to be factory installed. Must also specify cutout location on lectern.			
	1 x 6 x 6	2.0 / 3	66-FAN	
<b>Rack Cube</b> 	All metal construction providing front and rear Rack Rails allowing rack storage mounting prior to installation in rack storage compartment. Standard Black metal. Available with 6 RU - 14 RU; height varies by RU count. Complete Model number replacing blank "___" with desired RU (Ex: 66-RRCUBE10 - 10 RU Rack Cube). NOTE: If ordering with a lectern, specify "-RR" at end of lectern model number. (Ex: 66-LP303047LM-RR)			
	19 1/8 x 19 1/2 x Varies		66-RRCUBE___	